



13110 Emerson Rd, Apple Creek, OH 44606  
888-332-5534 | [info@crownplacebrands.com](mailto:info@crownplacebrands.com)  
[www.aladdinlamps.com](http://www.aladdinlamps.com)



## ASSEMBLY INSTRUCTIONS FOR YOUR NEW WALL BRACKET LAMP

Read these instructions and the **Operating and Safety Instructions** very carefully to ensure proper assembly and operation of this lamp. See page 2 for labeled diagram of parts.

1. **Ensure that the location you are mounting the wall bracket is structurally sound**, so that it will support 10-12 pounds of lamp and fuel.  
***Note:** It is recommended that the bracket be mounted on a wooden wall stud, instead of being mounted to the plaster wallboard. Two (2) wood screws have been provided for this purpose. If they are missing, you can use 8" x 1-1/2" brass or nickel wood screws.*
2. Place the Regency brass or Genie III series bowl on a level surface.
3. Set the shade tripod (1281 or N401N) on top of the bowl and hold it in place.\*
4. Screw the burner (100013606 or 100013607) into the bowl while you hold the shade ring in place.
5. Remove the filler plug/cap from the bowl and fill with K-1 kerosene or Aladdin lamp oil. Replace filler plug into the bowl.  
***Caution:** Do not fill above the lip of the oil fill opening.*  
***Note:** We do not recommend using any other lamp oil.*
6. Place the bowl into the ring of the wall bracket (N1188, N118N or 100004948).
7. Lock the mantle (R150) into the center of the gallery (N239AB or N239AN) with a clockwise turn. The gallery is located on the top of the burner.  
***Caution:** Do not touch the mesh part of the mantle. Use the wire frame to handle the mantle or you will damage it.*
8. Set the bottom of the chimney (100004908) into the gallery. Be sure not to touch the mantle during this process.
9. Place the shade into the tripod, so that the bottom of the shade sits inside the ring of the tripod.\*

*\*If your lamp does not include a shade, skip steps 3 and 9.*

### CAUTION

The heat from the lamp will make the chimney very hot. Therefore, the lamp must be mounted so that the top of the chimney is at least 36" away from the ceiling or any overhead objects.

When the lamp is in use, the gallery and chimney will become very hot. **DO NOT TOUCH** these areas until the lamp is extinguished and has been allowed to cool. Do not attempt to move the lamp until it has cooled.

*\*\*\*Please see the enclosed **Operating and Safety Instructions** for more information and tips on caring for your Aladdin lamp.\*\*\**

